

1     **METHOD OF TRANSMITTING LAYERED VIDEO-CODED INFORMATION**

2

3

4

5     **Technical Field**

6             Embodiments of the present invention relate to transmitting video  
7 information over a network. In particular, embodiments of the present  
8 invention relate to methods for setting a transmission priority for layered  
9 video-coded information that is to be transmitted over a network.

10

11     **Background of the Invention**

12             One of the most promising applications in the field of communications  
13 is the transmission of encoded or compressed video information across  
14 mediums such as telephone networks, cable television networks, and the  
15 Internet. The video information is typically encoded at one location,  
16 transferred over a network to a destination, and decoded at the destination.  
17 A video encoder may be used to, among other things, receive video signals  
18 and other data, convert these to digitized form (if the data is not already in  
19 digitized form), and compress the data using an encoding algorithm.  
20 Examples of video encoding algorithms are the MPEG-1, MPEG-2, and  
21 MPEG-4 digital video-coding standards of the Motion Picture Expert Group  
22 and the H.261 and H.264 standards from the ITU-T (International

1 Telecommunications Union--Telecommunications sector). The video  
2 information may be first obtained from a video camera that generates video  
3 signals which contain a series of video frames that each depict images. In  
4 addition, the video-coded information may also include other components  
5 such as, for example, animations, text, and/or audio information. A video  
6 decoder may be used at the destination to decode the received video-coded  
7 frames into a format that may be displayed by a video monitor or other  
8 device.

9 The networks over which video-coded information is transmitted  
10 generally have limited bandwidth. The amount of bandwidth available at any  
11 given time depends upon factors such as the amount of traffic and the  
12 operability of network components. The amount of available bandwidth is a  
13 major parameter for the quality of the video presented by the video decoder,  
14 with an increase in bandwidth increasing the quality of the video. The  
15 unavailability of bandwidth may cause video-coded frames to be lost or  
16 delayed while being sent across the network due to network congestion or  
17 buffer overflow. Such losses and delays may cause severe degradation in  
18 perceived quality of the video displayed by the video decoder and may result  
19 in error propagation, especially where the video is sent in real-time or  
20 streamed or where the video contains objects in motion.

21 One way to combat the impact of limited bandwidth is to use a  
22 "layered" video-coding scheme. Layered video-coding schemes divide a  
23 stream of video-coded frames into layers. In the standard layered video-  
24 coding scheme, the video-coded information signal is divided into a base  
25 layer and an enhancement layer. The enhancement layer typically provides  
26 refinement information that is added to the base layer to provide higher  
27 quality. For example, the base layer may typically be decoded and  
28 displayed without any data from the enhancement layer, although this would  
29 probably result in reduced picture quality. When network congestion occurs,  
30 packets may be dropped from the enhancement layer, but valid video at a  
31 slightly lower quality may still be produced by decoding packets from the  
32 base layer.

1 Traffic that is sent over a network is often classified by a priority level.  
2 In many networks, the priority level will be used if the network needs to drop  
3 some of the packets being transported. For example, if network congestion  
4 occurs and the network has to drop packets, the network will typically drop  
5 the lower level packets. A video encoder may take advantage of these  
6 classifications by designating some video-coded frames as high priority and  
7 the rest as low priority. For example, every fifth frame may be sent as high  
8 priority, with the rest being sent as low priority. A typical layered video-  
9 coding scheme is to transmit enhancement layer traffic over the network with  
10 a lower priority than the base layer. Another scheme, which is referred to as  
11 using multiple threads, codes the base layer frames independently, using  
12 only previous base layer frames for motion compensation, and codes the  
13 enhancement layer frames normally, using both base and enhancement  
14 layer frames for motion compensation.

15 A problem may occur when using a layered video-coding scheme if  
16 there are simultaneous attempts to transmit high priority base layer frames.  
17 If this occurs, the network may become overloaded with high priority data. In  
18 this case, either base layer frames may be lost, causing drastic quality  
19 reduction, or the network may be forced to buffer some of the base layer  
20 frames, causing excessive delays.

## 21 22 23 **Summary of the Invention**

24 Embodiments of the present invention alleviate degradation in a  
25 layered video-coded system by using feedback from the network indicating  
26 whether or not capacity is available for sending the high priority frames. The  
27 feedback may include a response to a request for information on whether the  
28 network currently has the available capacity to transmit additional high  
29 priority traffic. In an embodiment, a candidate base layer frame is  
30 transmitted over the network as a base layer frame if permission to send  
31 high priority data was granted and is transmitted over the network as an  
32 enhancement layer frame if permission to send high priority data was

denied. In a further embodiment, a candidate base layer frame is deleted if permission to send high priority data was denied.

### **Brief Description of the Drawings**

FIG. 1 is a block diagram of a system including a video encoder and decoder according to an embodiment of the present invention.

FIG. 2 is a block diagram of a video encoder according to an embodiment of the present invention.

FIGS. 3-7 are flow diagrams of methods of transmitting video information according to embodiments of the present invention.

### **Detailed Description of the Invention**

The present invention provides an improved method of transmitting layered video-coded data by using network feedback which indicates whether bandwidth is available to send high priority frames (e.g., base layer frames). In an embodiment, the encoder does not decide a priori which frames are to be transmitted as base layer frames, but rather requests permission from the network to transmit high priority data before encoding a candidate base layer frame. In this embodiment, the candidate base layer frame may either be encoded and transmitted as a base layer frame if permission to send high priority data is granted or may be transmitted as a low priority frame, or deleted from transmission, if permission to send high priority data was denied. This and other embodiments are described in more detail below. By using an embodiment of the present invention, the likelihood of network overload is minimized because the arrival of high priority data into the network is randomized. In addition, embodiments of the invention avoid buffering large amounts of data and thus avoid the delay that such buffering may cause. Use of the present invention may therefore alleviate degradation of perceived picture quality due to loss of frames or buffering delays.

FIG. 1 is a block diagram of a system including a video encoder and decoder according to an embodiment of the present invention. FIG. 1 shows a video encoder 110 and a video decoder 120 both of which are coupled to a network 130. The term "coupled" is intended to encompass and be broader than the term "directly connected." As discussed below, encoder 110 or another device may transmit video-coded data (such as video-coded frames 113) to decoder 120 across network 130 at a priority level that is determined using information about the network's available capacity (such as network capacity information 116). This information may be provided in response to a request for such information (such as network capacity request 115). Of course, the present invention is not limited to the system shown in FIG. 1. For example, in other embodiments, video-coded data may be sent by an encoder such as encoder 110 to devices other than a decoder. For example, encoder 110 may send video-coded data to a data storage facility for later use by a decoder. As another example, video-coded data may be sent from encoder 111 to a transmission device which transmits the data across the network. Similarly, in other embodiments, stored video-coded data that had been previously encoded may be transmitted to a decoder such as decoder 120 by a device other than an encoder.

Network 130 may be any information systems network across which information can be sent. Examples of network 130 include the Internet, an intranet, a wireline telephone network, a wireless telephone network, a virtual private network, or any combination of these networks. Encoder 110 may be used to encode video data, such as video signals 112, for transmission across a network as video-coded frames. Encoder 110 may output video-coded data that complies with a video-coding standard or algorithm such as MPEG-1, MPEG-2, MPEG-4, H.261, and H.264. In FIG. 1, encoder 110 is shown coupled to a video camera 111. In an embodiment, video camera 111 outputs video signals 112 to encoder 110. In other embodiments, encoder 110 may encode prerecorded video signals or may receive other types of input such as animation, text, or audio data. Decoder 120 may be used to receive and decode video-coded frames for display as

video images. Decoder 120 is shown coupled to monitor 121 and may output decoded video data, such as video signals 122, for display as video images on monitor 121.

As shown in FIG. 1, network 130 includes a network access server 131 that connects encoder 110 to network 130 and a network access server 132 that connects decoder 120 to network 130. Network access server 131 and network access server 132 may permit connections to network 130 from outside the network and may be operated by a third-party such as AT&T Corp.® or America Online, Inc.® Network 130 includes a network administrator 133 which administers operation of network 130. In an embodiment, network 130 may be decentralized and may contain multiple network administrators. Fig. 1 shows a high priority channel 134 and a low priority channel 136 coupling network access server 131 to network access server 132. In an embodiment, high priority channel 134 and a low priority channel 136 are logical paths across network 130, and data may be transmitted across each logical path using various physical paths. In an embodiment, network 130 contains a plurality of virtual circuits that may be used to transmit high priority traffic and a plurality of virtual circuits that may be used to transmit low priority traffic. In an embodiment, network 130 contains a plurality of nodes, such as router or switches, and many of these nodes may be used to transmit data for both high priority channel 134 and low priority channel 136.

A person of skill in the art would appreciate that the amount of traffic across network 130 may be dynamic, and thus that the amount of available bandwidth may be constantly changing over time. At any given time, network 130 may experience congestion and may be unable to provide bandwidth for transmitting additional data. When network congestion occurs, network 130 may take appropriate actions such as dropping data or buffering data. For example, if a data packet XYZ is sent from network access server 131 to be forwarded across network 130 to network access server 132, but network 130 does not have the bandwidth to transmit data packet XYZ, then data packet XYZ may be dropped and a message

1 indicating this dropping may be transmitted back to encoder 110. In an  
2 embodiment, network 130 will drop low priority packets before dropping a  
3 high priority packet. Network 130 may impose an additional charge for the  
4 transmission of data on a high priority channel.

5 In an embodiment, network administrator 133 maintains information  
6 about the amount of currently available network bandwidth and may provide  
7 information about current network capacity and expected future network  
8 capacity as feedback to encoder 110. For example, encoder 110 may send  
9 a network capacity request 115 through network access server 131 to  
10 network administrator 133, and in response network administrator 133 may  
11 send network capacity information 116 through network access server 131 to  
12 encoder 110. Network capacity request 115 may be a request for  
13 information about the availability of capacity to send a type of data (e.g., a  
14 high priority frame or base layer frame), and network capacity information  
15 116 may be a response to such a request. In an embodiment, a request for  
16 information sent from encoder 110 does not specify the type of data to be  
17 transmitted (e.g., that the data is video-coded frames) and may be, for  
18 example, a request for a specified amount of bandwidth. In this example,  
19 the priority of the bandwidth, the size of the data, and/or the duration may be  
20 specified. In an embodiment, a request is not required for the sending of  
21 network capacity information 116, and network capacity information may be  
22 sent, for example, on a periodic basis or during conditions determined by  
23 network administrator 133. Of course, a person of ordinary skill in the art  
24 would appreciate that network capacity request 115 and network capacity  
25 information 116 may be transmitted between encoder 110 and network  
26 access server 131 using the same connection as the video-coded frames  
27 113. Embodiments of the present invention that make use of this network  
28 capacity information when transmitting video-coded information are further  
29 described below.

30 FIG. 2 is a block diagram of a video encoder according to an  
31 embodiment of the present invention. FIG. 2 shows an encoder 110 such as  
32 in FIG. 1 above. In addition, FIG. 2 shows a stream of video signals 112 that

1 is coded by encoder 110 and transmitted as a stream of video-coded frames  
2 113 across network 130 over two logical channels (high priority channel 134  
3 and low priority channel 136). FIG. 2 shows six video frames that may be  
4 part of the same stream of video data. The first four frames in the stream  
5 (i.e., 1<sup>st</sup> video frame 221, 2<sup>nd</sup> video frame 222, 3<sup>rd</sup> video frame 223, and 4<sup>th</sup>  
6 video frame 224) have already been encoded and are being transmitted over  
7 network 130, while the other two frames (5<sup>th</sup> video frame 225 and 6<sup>th</sup> video  
8 frame 226) consist of uncoded data that is being transmitted for coding to  
9 encoder 110 by, for example, video camera 111 of FIG. 1. Of course, each  
10 of the video-coded frames may comprise multiple frames of uncoded video  
11 data. As discussed above, the video-coded frames may also include non-  
12 video information such as animations, text, control information, and/or audio  
13 information. In the embodiment shown, each of the video-coded frames 113  
14 transmitted across network 130 contain a priority level field. A frame that  
15 has a low priority level such as 2<sup>nd</sup> video frame 222 is transmitted on low  
16 priority channel 136. In an embodiment, the priority level is built into the  
17 video-coded frame when it is encoded. In other embodiments, the priority  
18 level may be added to a video-coded frame after the frame is encoded or  
19 may be transmitted to network 130 as a data element separate from the  
20 video-coded frame.

21 As shown in FIG. 2, encoder 110 contains encoding logic 117 and  
22 transmission priority setting logic 118. Encoding logic 117 may be used to  
23 encode the video data. Transmission priority setting logic 118 may send  
24 network capacity requests 115 and may receive network capacity  
25 information 116 in response to these requests. Transmission priority setting  
26 logic 118 may use the network capacity information to select a transmission  
27 priority for each of the video-coded frames 113 according to an embodiment  
28 of the present invention such as the method discussed below. Of course,  
29 encoder 110 may contain additional components such as logic to control the  
30 transmission of data to network 130. As would be appreciated by a person  
31 of ordinary skill in the art, encoder 110 may also contain an analog-to-digital  
32 converter, transform logic, quantizer logic, and prediction logic. The



1 components in encoder 110 may be embodied in software, hardware,  
2 firmware, or some combination. Encoder 110 may include one or more  
3 central processing units (CPUs), random access memories (RAMs), and  
4 Read Only Memories (ROMs), and memories in encoder 130 may store  
5 instructions to be executed by a processor to carry out embodiments of the  
6 invention as described herein. The logic in encoder 110 may be embodied  
7 in a special purpose processing unit such as an application specific integrated  
8 circuit (ASIC). In an embodiment, encoder 110 is a personal computer (PC)  
9 that contains software to carry out an embodiment of the present invention.

10 FIG. 3 is a flow diagram of a method of transmitting video information  
11 according to an embodiment of the present invention. The description below  
12 is explained with reference to the systems shown in FIGS. 1 and 2, but of  
13 course these methods may be used with other systems. As shown in FIG. 3,  
14 a frame of video data to be coded as video-coded data is received (301).  
15 For example, a frame of video data may be received at encoder 110 from  
16 video camera 111 or may be received from a buffer in another part of  
17 encoder 110. In embodiments, the frames of video data may already be  
18 stored at the encoder (e.g., buffered at the encoder) prior to coding. The  
19 encoder may send a request for information relating to the network's  
20 available capacity to transmit high priority data (302), and capacity  
21 information may be received in response to the request (303). Examples of  
22 the request and response are shown in FIG. 1 as network capacity requests  
23 115 and network capacity information 116. In an embodiment, network  
24 administrator 133 will determine if the capacity to send high priority data is  
25 available and will send a response to encoder 110. If the response indicates  
26 that the network has the capacity to transmit the frame as high priority data  
27 (304), then the frame is encoded as a high priority frame (e.g., a base layer  
28 frame) (305) and is transmitted as high priority data (306). If the response  
29 indicates that the network does not have the capacity to transmit high priority  
30 data (304), then the frame is encoded as a low priority frame (e.g., an  
31 enhancement layer frame) (307) and is transmitted as low priority data (308).  
32 Frames that are transmitted as high priority data may use a high priority

channel across network 130 and frames that are transmitted as low priority data may use a low priority channel across network 130.

FIG. 4 is a flow diagram of a method of transmitting video information according to another embodiment of the present invention. As in the previous embodiment, the encoder may receive a frame of video data to be coded as video-coded data (401), may send a request for information relating to the network's available capacity to transmit high priority data (402), and may receive capacity information in response to the request (403). In this embodiment, the data is video-coded (404) and the video-encoded frame is buffered (405) at substantially the same time as the request is sent and/or the response to the request is received. If the network has the capacity to transmit the frame as high priority data (406), then the request is transmitted as high priority data (407). If the network does not have the capacity to transmit high priority data (406), then the video frame is transmitted as low priority data (408). In some embodiments, such as very high compression codecs, the frame has to be recoded as a high priority frame. In other embodiments, the frame may have been coded at both priorities (high and low) in parallel, and the frame with the desired priority may be chosen at a later time.

FIG. 5 is a flow diagram of a method of transmitting video information according to another embodiment of the present invention. FIG. 5 contains steps 401 to 407 as in FIG. 4. In this embodiment, however, the encoded frame is deleted from transmission (500) if the network does not have the capacity to transmit high priority data. When an encoded frame is deleted from transmission, the video data may be lost, but such a loss may not greatly impact perceived picture quality as long as the encoder 110 is aware of the loss.

FIG. 6 is a flow diagram of a method of transmitting video information according to another embodiment of the present invention. As discussed above, a frame of video data to be coded as video-coded data may be received (601). In this embodiment, the frame is then encoded as a high priority frame (602). In this embodiment, all frames may be encoded as high

1 priority frames prior to requesting and/or receiving any information about  
2 available network capacity. As shown in FIG. 5, after encoding the high  
3 priority frame, a request for information relating to the network's available  
4 capacity to transmitting high priority data is sent (603), and capacity  
5 information is received in response to the request (604). If the network has  
6 the capacity to transmit the frame as high priority data (605), then the  
7 request is transmitted as high priority data (606). If the network does not  
8 have the capacity to transmit high priority data (605), then the video frame is  
9 transmitted as low priority data (607).

10 FIG. 7 is a flow diagram of a method of transmitting video information  
11 according to another embodiment of the present invention. A frame of video  
12 data to be coded as video-coded data may be received (701). In this  
13 embodiment, frames are encoded as either high priority frames or low  
14 priority frames based on a priority selection algorithm (702). The algorithm  
15 may use information about how much bandwidth is allocated for the  
16 transmission of high priority frames. The encoder then obtains information  
17 relating to the network's available capacity to transmit high priority data  
18 (703). This information may be obtained by network feedback or other  
19 means such as the Real Time Control Protocol (RTCP) from the Internet  
20 Engineering Task Force (IETF). If more than a threshold number of low  
21 priority frames have been lost (704), then an additional number of the frames  
22 may be encoded as high priority frames than is dictated by the transmission  
23 priority algorithm discussed above. These additional high priority frames  
24 may be encoded at a lower quality than is generally used for high priority  
25 frames.

26 The present invention improves the transmission of video information  
27 by using network feedback on available bandwidth. Through the use of  
28 feedback the present invention allows for the randomization of the arrival of  
29 high priority data into the network and, therefore, minimizes the likelihood of  
30 network overload. The present invention may also avoid the buffering of  
31 large amounts of data and the ensuing delay that such buffering may cause.  
32 Several embodiments of the present invention are specifically illustrated

1 and/or described herein. However, it will be appreciated that modifications  
2 and variations of the present invention are covered by the above teachings  
3 and within the purview of the appended claims without departing from the  
4 spirit and intended scope of the invention. For example, unless otherwise  
5 specified, the order of the steps performed may be varied.

TOPTON : 30000000